

## Trek Fuel EX

Rahmengrößennummer	15.5	15.5	17.5	17.5	18.5	18.5	19.5	19.5	21.5	21.5
Rahmengrößenbuchstabe	S	S	M	M	ML	ML	L	L	XL	XL
Geometrieposition	Hoch	Gering	Gering	Hoch	Gering	Hoch	Gering	Hoch	Gering	Hoch
Lauftradgröße	29"	29"	29"	29"	29"	29"	29"	29"	29"	29"
A – Sitzrohr	39.5	39.5	42.0	42.0	43.5	43.5	45.0	45.0	50.0	50.0
B – Sitzwinkel	68.0°	67.5°	67.5°	68.0°	67.5°	68.0°	67.5°	68.0°	67.5°	68.0°
Effektiver Sitzwinkel	75.5°	75.0°	75.0°	75.5°	75.0°	75.5°	75.0°	75.5°	75.0°	75.5°
C – Steuerrohrlänge	10.0	10.0	10.0	10.0	10.5	10.5	10.5	10.5	12.0	12.0
D – Lenkwinkel	66.5°	66.0°	66.0°	66.5°	66.0°	66.5°	66.0°	66.5°	66.0°	66.5°
E – Effektives Oberrohr	57.7	57.8	60.3	60.2	61.9	61.8	63.4	63.3	66.3	66.2
F – Tretlagerhöhe	34.6	34.0	34.0	34.6	34.0	34.6	34.0	34.6	34.0	34.6
G – Tretlagerabsenkung	2.8	3.4	3.4	2.8	3.4	2.8	3.4	2.7	3.4	2.7
H – Kettenstrebenlänge	43.6	43.7	43.7	43.6	43.7	43.6	43.7	43.6	43.7	43.6
I – Offset	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3
J – Trail	11.5	11.9	11.9	11.6	11.9	11.6	11.9	11.6	11.9	11.6
K – Radstand	115.3	115.4	117.9	117.8	119.6	119.5	121.1	121.0	124.2	124.1
L – Überstandshöhe	70.7	70.1	74.2	74.8	74.5	75.1	75.0	75.6	76.2	76.8
M – Rahmen-Reach	42.0	41.5	44.0	44.5	45.5	46.0	47.0	47.5	49.5	50.0
N – Rahmen-Stack	60.5	60.9	60.9	60.5	61.3	60.9	61.3	60.9	62.7	62.3

